



Within Australia Ph: 1800 ARROW KARTS

or visit

www.arrowkarts.com

KART SET UP SHEET

Kart Model: Test Kart Driver: B. Price

Class: Rotax Light Event: Rotax Nationals Todd Rd Date: 07/09/2008

AXLE SIZE: 50mm AXLE LENGTH: 1030mm AXLE TYPE: Soft

- NUMBER OF REAR AXLE BEARINGS: 3
- FRONT CRASH BAR: TIGHT X LOOSE _____ (Loose Front Hoop)
- REAR CRASH BAR: TIGHT _____ LOOSE X
- FRONT TRACK: 10 mm OF SPACERS INSIDE WHEEL.
- REAR TRACK: 1380 mm OVERALL WIDTH TO OUTSIDE EDGE OF WHEELS.
- FRONT WHEEL ALIGNMENT: ZERO _____ TOE IN _____ mm TOE OUT 2 mm
- FRONT CASTOR: MINIMUM _____ CENTRAL X MAXIMUM _____
- FRONT CAMBER: ZERO _____ POSITIVE 6 mm NEGATIVE _____ mm
- STUB AXLE: INNER _____ OUTER _____
- TIE ROD MOUNTING HOLE: INNER X MIDDLE _____ OUTER _____
- SEAT POSITION: A 23 mm B 210 mm C 90 mm
- SEAT STAYS: TIGHT X LOOSE _____ 2 OR 4? 2
- SIDE TORSION BAR: IN _____ OUT _____
- FRONT TORSION BAR / CLAMP: IN _____ OUT _____
- REAR TORSION BAR: OUT X VERTICAL _____ FLAT _____
- REAR CIK CROSS BAR: TIGHT _____ LOOSE _____ REMOVED X
- TYRE PRESSURE: FRONT LEFT 15(Cold) FRONT RIGHT 14(Cold) PSI OR BAR? PSI
- TYRE PRESSURE: REAR LEFT 15(Cold) REAR RIGHT 13.5(Cold) PSI OR BAR? PSI
- WHEEL FRONT TYPE: _____ Douglas Magnesium Solid
- WHEEL REAR TYPE: _____ Douglas Magnesium Solid
- FRONT HUB LENGTH: 65MM
- REAR HUB LENGTH: 110MM (Inner Bolt Only)
- SIDE POD BARS: LOOSE X TIGHT _____
- FRONT RIDE HEIGHT: LOW X MIDDLE _____ HIGH _____
- REAR RIDE HEIGHT: LOW _____ MIDDLE X HIGH _____

OTHER SPECIAL DETAILS: Tyre: Mojo D2

