



SEAT FITTING INSTRUCTIONS FOR STANDARD SEATS.

**** PLEASE READ THE FOLLOWING BEFORE FITTING SEAT ****



DUE TO THE FACT THAT WE ENDEAVOUR TO MAKE SEATS AS LIGHT AS POSSIBLE WHILST STILL BEING SERVICEABLE IT IS IMPERATIVE THAT THE FOLLOWING FITTING INSTRUCTIONS ARE FOLLOWED.

SIDE MOUNTING HOLES

- USE SEAT ALLOY SEAT STRENGTHENING DISCS (P/CODE. SE74, SE74B or SE74P)
- USE ALLOY COUNTERSUNK WASHERS (P/CODE. SE72, SE72B or SE72P)
- ENSURE "AT ALL TIMES" THAT MOUNTS ARE ALIGNED WITH SEAT. RECOMMENDED/OPTIONAL - SELF ALIGNING WASHERS (P/CODE. SE73S, SE73B or SE73SB & SE73L)

FORWARD MOUNTING HOLES

- PLASTIC COUNTERSUNK WASHERS ARE ACCEPTABLE ON THE FRONT MOUNTING POINTS. (P/CODE. SE71/SE71R)
- ENSURE "AT ALL TIMES" THAT MOUNTS ARE ALIGNED WITH SEAT. ie, BEND IF NECESSARY &/or USE TAPERED SEAT WASHERS. (P/CODE. SE70/SE70R)

IT IS ESSENTIAL THAT THE FIBRE GLASS IS NOT STRAINED DUE TO MISALIGNED BRACKETS &/or SPACERS AS THIS WILL RESULT IN SEAT FAILURE. IT IS ALSO A FACT THAT HIGHLY STRESSED MISALIGNED SEATS CAN HAVE A NEGATIVE EFFECT ON KART PERFORMANCE.