



Within Australia Ph: 1800 ARROW KARTS

or visit

www.arrowkarts.com

## KART SET UP SHEET

Kart Model: X1e - cik Driver: \_\_\_\_\_

Class: Leopard Light Event: \_\_\_\_\_ Date: \_\_\_\_\_

AXLE SIZE: 50mm AXLE LENGTH: 1030mm AXLE TYPE: Medium

- NUMBER OF REAR AXLE BEARINGS: 3
- FRONT CRASH BAR: TIGHT \_\_\_\_\_ LOOSE X
- REAR CRASH BAR: TIGHT X LOOSE \_\_\_\_\_
- FRONT TRACK: 30 mm OF SPACERS INSIDE WHEEL.
- REAR TRACK: 1395 mm OVERALL WIDTH TO OUTSIDE EDGE OF WHEELS.
- FRONT WHEEL ALIGNMENT: ZERO \_\_\_\_\_ TOE IN \_\_\_\_\_ mm TOE OUT 2 mm
- FRONT CASTOR: MINIMUM \_\_\_\_\_ CENTRAL \_\_\_\_\_ MAXIMUM \_\_\_\_\_
- FRONT CAMBER: ZERO X POSITIVE \_\_\_\_\_ mm NEGATIVE \_\_\_\_\_ mm
- STUB AXLE: INNER \_\_\_\_\_ OUTER \_\_\_\_\_
- TIE ROD MOUNTING HOLE: INNER X MIDDLE \_\_\_\_\_ OUTER \_\_\_\_\_
- SEAT POSITION: A 23 mm B 200 mm C 90 mm
- SEAT STAYS: TIGHT X LOOSE \_\_\_\_\_ 2 OR 4? 2
- SIDE TORSION BAR: IN \_\_\_\_\_ OUT \_\_\_\_\_
- FRONT TORSION BAR / CLAMP: IN \_\_\_\_\_ OUT \_\_\_\_\_
- REAR TORSION BAR: OUT X VERTICAL \_\_\_\_\_ FLAT \_\_\_\_\_
- REAR CIK CROSS BAR: TIGHT \_\_\_\_\_ LOOSE X REMOVED \_\_\_\_\_
- TYRE PRESSURE: FRONT LEFT 8.5 FRONT RIGHT 9 PSI OR BAR? PSI
- TYRE PRESSURE: REAR LEFT 8 REAR RIGHT 8.25 PSI OR BAR? PSI
- WHEEL FRONT TYPE: Douglas Magnesium Solid
- WHEEL REAR TYPE: Douglas Magnesium Solid
- FRONT HUB LENGTH: 80MM
- REAR HUB LENGTH: 90MM
- SIDE POD BARS: LOOSE \_\_\_\_\_ TIGHT X
- FRONT RIDE HEIGHT: LOW \_\_\_\_\_ MIDDLE X HIGH \_\_\_\_\_
- REAR RIDE HEIGHT: LOW \_\_\_\_\_ MIDDLE X HIGH X

OTHER SPECIAL DETAILS: Tyre: MG Yellow